



# Lexmark CX431adw

Small workgroup colour versatility is easy to deploy and share with the compact, lightweight Lexmark CX431adw multifunction, offering output at up to 24 ppm\*.

## Part Number

40N9573

## Print Technology

Colour Laser

## Function

Colour Copying, Colour Printing, Colour Scanning, Faxing

## Workgroup Size

Small-Medium Workgroup

## Touch Screen Display

Yes

## Display

7.2 cm LCD touch panel

## Print Speed (A4, Black)

Up to 24.7 ppm<sup>4</sup>

## Print Speed (A4, Colour)

Up to 24.7 ppm<sup>4</sup>

## Print Speed (A4, Black) Duplex

Up to 13 spm<sup>4</sup>

## Print Speed (A4, Colour) Duplex

Up to 13 spm<sup>4</sup>

## Time to First Page (Black)

As fast as 10.8 seconds

## Time to First Page (Colour)

As fast as 11 seconds

## Duplex (2-sided) Printing

Integrated Duplex

## Print Resolution, Black

4800 CQ (2400 x 600 dpi)

## Print Resolution, Colour

4800 CQ (2400 x 600 dpi)

## Copy Speed (A4, Black)

Up to 24.7 cpm<sup>4</sup>

## Copy Speed (A4, Colour)

Up to 24.7 cpm<sup>4</sup>

## Copy Speed (A4, Black) Duplex

Up to 24.7 spm<sup>4</sup>

## Copy Speed (A4, Colour) Duplex

Up to 24.7 spm<sup>4</sup>

## Time to First Copy (Black)

As fast as 12.1 seconds

## Time to First Copy (Colour)

As fast as 13.3 seconds

## Reduce / Enlarge Range

25 - 400 %

## A4/Ltr Simplex Scan Speed (Black)

Up to 45 / 48 sides per minute

## Scan Speed (A4/Ltr, Colour)

Up to 20 / 21 sides per minute

## A4/Ltr Duplex Scan Speed (Black)

Up to 90 / 96 sides per minute

## Duplex Scan Speed (A4/Ltr, Colour)

Up to 40 / 42 sides per minute

## Scan Area, Maximum (mm)

216 x 356 mm

## ADF Scan

DADF (single pass Duplex)

## Scanner Type

Flatbed scanner with ADF

## Scan Technology

CIS

## Scan Resolution, Enhanced

Up to 600 X 600 dpi

## Scan Resolution, Optical

Up to 600 dpi

## Scan File Formats (Send as)

JPEG, JPG, PDF, TIFF

## Scan Destinations

e-mail, FTP, USB Flash drive, USB or Network connected computer

## Modem Speed

Max is 33,600 bps, V.34 Half-Duplex Kbps

## Fax Transmission Speed

< 3 seconds per page

## Processor Speed

Dual Core, 1.0 GHz

## Memory, Standard

1 GB

## Memory, Maximum

1 GB

## Hard Disk

Not Available

## Apple Operating Systems Supported

Support is provided through AirPrint and AirScan only

## Citrix MetaFrame

Microsoft Windows Server 2012 R2 Datacenter Edition running Citrix XenApp 7.5, 6, 7, 8, 9, 11, 12, 13, 14, 15, 16, Microsoft Windows Server 2012 Datacenter Edition running Citrix XenApp 7.5, 6, 7, 8, 9, 11, 12, 13, 14, 15, 16, Microsoft Windows Server 2012 Foundation running Citrix XenApp 6.0, 6.5, Microsoft Windows Server 2012 Essentials running Citrix XenApp 6.0, 6.5, Microsoft Windows Server 2012 Standard running Citrix XenApp 6.0, 6.5

## Linux Operating Systems Supported

Ubuntu 20.04, Debian 10, SUSE Linux Enterprise Server 12 SP5, OpenSUSE 15.2, Debian 11, Ubuntu 22.04, Fedora 36, Fedora 37, SUSE Linux Enterprise Server 15 SP4, OpenSUSE 15.4, Red Hat Linux 8.7, Red Hat Linux 9.1

## Microsoft Windows Operating Systems Supported

Windows 7, Windows 7 x64, Windows 8, Windows 8 x64, Windows Server 2012, Windows 8.1, Windows Server 2012 R2, Windows 10, Windows Server 2016, Windows Server 2019, Windows Server 2022, Windows 11

## Novell Operating Systems Supported

Novell NetWare 6.5 Open Enterprise Server, Novell Open Enterprise Server 2 (SP3) on SuSE Linux Enterprise Server 10 SP4 (x86 and x64) 3, Novell Open Enterprise Server 11 (SP3) on SuSE Linux Enterprise Server 11 SP4 (x86 and x64), Novell Open Enterprise Server 11 (SP3) on SuSE Linux Enterprise Server 12 SP1 (x86 and x64), Novell Open Enterprise Server 15 (SP1) on SuSE Linux Enterprise Server 11 SP4 (x86 and x64)

## Included Paper Handling

250-Sheet Input, Integrated Duplex, Single-Sheet Manual Feed, 100-Sheet Output Bin

## Optional Paper Handling

250-Sheet Tray

## Paper Input Capacity, Standard

Up to 250+1 pages 75 gsm bond

## Paper Input Capacity, Maximum

Up to 750+1 pages 75 gsm bond

## Paper Output Capacity, Standard

Up to 100 pages 75 gsm bond

## Paper Output Capacity, Maximum

Up to 100 pages 75 gsm bond

## Paper Weight Range Supported - Standard Tray (gsm)

60 - 162 gsm

## ADF

50-Sheet Automatic Document Feeder

## ADF Paper Input Capacity

Up to 50 pages 75 gsm bond

## ADF Paper Output Capacity

Up to 50 pages 75 gsm bond

## Finishing Option

No

## Number of Paper Inputs, Standard

2

## Number of Paper Inputs, Maximum

2

## Media Types Supported

Card Stock, Envelopes, Glossy paper, Paper Labels, Plain Paper, Hagaki Card, Refer to the Paper & Specialty Media Guide

## Media Sizes Supported

10 Envelope, 7 3/4 Envelope, 9 Envelope, A4, A5, B5 Envelope, C5 Envelope, DL Envelope, Hagaki Card, Executive, Folio, JIS-B5, Legal, Letter, Statement, Universal, Oficio, A6

## Standard Ports

USB 2.0 Specification Hi-Speed Certified (Type B), Gigabit Ethernet (10/100/1000), Front Hi-Speed USB port Compatible with USB 2.0 Specification (Type A), 802.11ac Wireless

## Direct USB

Yes

## Ethernet Network

Yes

**Wireless**

Yes

**Network Protocol Support**

TCP/IP IPv4, TCP/IP IPv6, TCP, UDP

**Network Printing Methods**

Enhanced IP (Port 9400), FTP, TFTP, IPP 1.0, 1.1, 2.0 (Internet Printing Protocol), Microsoft Web Services WSD

**Network Management Protocols<sup>1</sup>**

HTTP, HTTPS (SSL/TLS), SNMPv1, SNMPv2c, SNMPv3, WINS, IGMP, BOOTP, RARP, APIPA (AutoIP), DHCP, ICMP, DNS, DDNS, mDNS, ARP, NTP, Finger,

**Network Security**

SNMPv3, TCP/IP port access control, 802.1x Authentication: MD5, MSCHAPv2, LEAP, PEAP, TLS, TTLS, IPsec

**Printable Area (metric)**

4.2 mm of the top, bottom, right and left edges (within)

**Printer Languages (Standard)**

PCL 5c Emulation, PCL 5e Emulation, PCL 6 Emulation, PostScript 3 Emulation, Direct Image, PDF 1.7 emulation, PCLm

**Fonts and Symbol Sets**

3 of 9 scalable PCL 5e fonts in Narrow, Regular and Wide, 2 PCL bitmap fonts, OCR-A, OCR-B scalable PCL 5e fonts, For more information, refer to the Technical Reference., 91 scalable PostScript fonts, 89 scalable PCL fonts

**Laser Cartridge Yields (up to)**

1,500-page Black and Colour (CMYK) Cartridges, 6,000-page Black Extra High Yield Cartridge, Average continuous cartridge yield is stated number of standard pages as listed. Declared yield value in accordance with ISO/IEC 19798., 6,700-page Colour (CMY) Extra High Yield Cartridges

**Cartridge(s) Shipping with Product**

1,500-page Colour (CMY) Return Program Toner Cartridges, 1,500-page Black Return Program Toner Cartridge

**Replacement Cartridges:**

Product functions only with replacement cartridges designed for use in a specific geographical region. See [www.lexmark.com/](http://www.lexmark.com/) regions for more details.

**Packaged Size (mm - H x W x D)**

519 x 440 x 556 mm

**Packaged Weight, kg**

22.7 kg

**Size (mm - H x W x D)**

344.4 x 411.2 x 394.1 mm

**Weight**

19.4 kg

**Noise Level, Idle**

14 dBA

**Noise Level (Print), Operating**

51/52 dBA

**Duplex Print Noise Level, Operating**

50/52 dBA

**Noise Level (Copy), Operating**

dBA

**Noise Level (Scan), Operating**

dBA

**Quiet Mode**

45 dBA

**ENERGY STAR**

Yes

**Average Power (Hibernate Mode)**

watts

**Average Power (Sleep Mode)**

1.3 watts

**Average Power (Ready Mode)**

17.5 watts

**Average Power (Printing)**

400 watts

**Average Power while Printing Duplex**

275 watts

**Average Power (Copying)**

395 watts

**Average Power (Scanning)**

21 watts

**ENERGY STAR Typical Electricity****Consumption (TEC)**

0.37 kilowatt-hours per week

**Product Warranty**

1-Year Onsite Service, Next Business Day

**Product Certifications**

ENERGY STAR, ICES-003 Class B, BSMI Class B, US FDA, UL 60950-1, FCC Class B, cUL CAN/CSA-C22.2 60950-1, CB EN/IEC 60950-1, CB EN/IEC 60825-1, CE DoC (EN 62301 Class B, EN 62311, CE EN/IEC 60950-1, CE EN/IEC 60825-1, EN 61000-3, EN 55022 Class B, EN 55024, UL), EFTA (CE), KCC, CCC, CECP, CEL, C-tick DoC, UL-AR, KC mark, UL GS mark, UCRF, EC 1275, DE-UZ 219, CNS-13438/14336, Wi-Fi CERTIFIED, China Green Product (CGP), Mopria Certified

**Maximum Monthly Duty Cycle**

Up to 75000 pages per month<sup>3</sup>

**Recommended Monthly Page Volume**

750 - 5000 pages<sup>2</sup>

**Specified Operating Environment**

Humidity: 8 to 80% Relative Humidity, Altitude: 0 - 3048 metres, Temperature: 10 to 32°C (50 to 90°F)

**License/Agreement Terms**

Printers are sold subject to certain license/ agreement conditions. See [www.lexmark.com/](http://www.lexmark.com/) printerlicense for details.

**Country of Origin**

China (PRC)

**UNSPSC Code**

43212110

<sup>1</sup>This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (<http://www.openssl.org/>)

<sup>2</sup>"Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage.

<sup>3</sup>"Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs.

<sup>4</sup>Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: [www.lexmark.com/ISOspeeds](http://www.lexmark.com/ISOspeeds).



Callout	Availability	Description
1	Standard	7.2 cm LCD touch panel
2	Standard	250-Sheet Tray
3	Optional	Optional 250 Sheet tray
4	Optional	

<b>P/N</b>	<b>Toner Cartridges</b>
20N0W00	Lexmark 20N0W00 Waste Print Bottle
20N30C0	Lexmark 20N30C0 Cyan Return Program Print Cartridge
20N30M0	Lexmark 20N30M0 Magenta Return Program Print Cartridge
20N30Y0	Lexmark 20N30Y0 Yellow Return Program Print Cartridge
20N30K0	Lexmark 20N30K0 Black Return Program Print Cartridge
20N3XC0	Lexmark 20N3XC0 Cyan Extra High Yield Return Programme Print Cartridge
20N3XM0	Lexmark 20N3XM0 Magenta Extra High Yield Return Programme Print Cartridge
20N3XY0	Lexmark 20N3XY0 Yellow Extra High Yield Return Programme Print Cartridge
20N3XK0	Lexmark 20N3XK0 Black Extra High Yield Return Programme Print Cartridge
20N0X20	Lexmark 20N0X20 Cyan Extra High Yield Print Cartridge
20N0X30	Lexmark 20N0X30 Magenta Extra High Yield Print Cartridge
20N0X40	Lexmark 20N0X40 Yellow Extra High Yield Print Cartridge
20N0X10	Lexmark 20N0X10 Black Extra High Yield Print Cartridge

<b>P/N</b>	<b>Paper Handling</b>
40N4250	250-Sheet Tray

<b>P/N</b>	<b>Furniture</b>
40C2300	Adjustable Stand

<b>P/N</b>	<b>Connectivity</b>
1021294	USB (2 Meter) Cable

<b>P/N</b>	<b>Extended Warranties</b>
2371567	CX431 1-Year Onsite Service Renewal NBD
2371568	CX431 2-Year Onsite Service Renewal NBD
2371569	CX431 3-Year Onsite Service Renewal NBD
2371570	CX431 4-Year Onsite Service Renewal NBD
2371571	CX431 Per Call 1-Time Onsite Repair NBD Warranty
2371572	CX431 1 Year Post Warranty Onsite Repair NBD
2371561	CX431 2-Years Total (1+1) Onsite Service
2371562	CX431 3-Years Total (1+2) Onsite Service
2371563	CX431 4-Years Total (1+3) Onsite Service
2371564	CX431 5-Years Total (1+4) Onsite Service
2371565	CX431 6-Years Total (1+5) Onsite Service
2371566	CX431 7-Years Total (1+6) Onsite Service