



Lexmark CS622de

Colour output of up to 40 [38] pages per minute*, toner savings and 4.3-inch [10.9 cm] colour touch screen come together in the Lexmark CS622de.

Part Number

42C0090

Print Technology

Colour Laser

Workgroup Size

Small-Medium Workgroup

Touch Screen Display

Yes

Display

Lexmark e-Task 4.3-inch (10.9 cm) colour touch screen

Print Speed (A4, Black)

Do 38 ppm⁶

Print Speed (A4, Colour)

Do 38 ppm⁶

Hitrost tiskanja (A4, Črno) Duplex

Do 19 spm⁶

Hitrost tiskanja (A4, Barvno) Duplex

Do 19 spm⁶

Time to First Page (Black) As fast as

Hitrost: < 7 sekund

Time to First Page (Colour) As fast as

Hitrost: < 7 sekund

Duplex (2-sided) Printing

Integrated Duplex

Print Resolution, Black

1200 x 1200 dpi, 4800 CQ (2400 x 600 dpi)

Print Resolution, Colour

1200 x 1200 dpi, 4800 CQ (2400 x 600 dpi)

Processor Speed

Dual Core, 1.0 GHz

Memory, Standard

1024 MB

Memory, Maximum

1024 MB

Hard Disk

Option available

Apple Operating Systems Supported

Apple OS X (10.6, 10.7, 10.8, 10.9, 10.10, 10.11, 10.12, 10.13)

Citrix MetaFrame

Microsoft Windows 2000 Server running Terminal Services with Citrix MetaFrame XP Presentation Server or Citrix MetaFrame Presentation Server 3.0., Microsoft Windows 2000 Server running Terminal Services with Citrix Presentation Server 4.0, Microsoft Windows 2000 Server running Terminal Services with Citrix Presentation Server 3.0, 4.0, Microsoft Windows Server 2012 with Citrix XenApp 6.0, 6.5

Podprti Linux operacijski sistemi

Debian GNU/Linux 7.0, 8.0, SUSE Linux Enterprise Server 10, 11, 12, openSUSE 13.1, 13.2, Ubuntu 16.04 LTS, Fedora 23, 24, Red Hat Enterprise Linux WS 6, 7, openSUSE Linux 42.3

Podprti Microsoft Windows operacijski sistemi

Windows 7, Windows 7 x64, Windows 8, Windows 8 x64, Windows 8.1, Windows 8.1 x64, Windows 10

Podprti Novell operacijski sistemi

Novell NetWare 6.5 Open Enterprise Server, Novell NetWare 5.1(SP 6+), 6.0(SP 3+) with Novell Distributed Print Services (NDPS), Novell Open Enterprise Server on SUSE Linux Enterprise Server, Novell Open Enterprise Server 2 on SUSE Linux Enterprise Server 10 SP4, Novell Open Enterprise Server 11 on SUSE Linux Enterprise Server 11, Novell Open Enterprise Server 2 SP2 on SuSE Linux Enterprise Server 10 SP3 3

Podprti UNIX operacijski sistemi

Sun Solaris x86 10, 11, Sun Solaris SPARC 10, 11, IBM AIX 6.1, 7.1

Included Paper Handling

250-Sheet Input, 125-Sheet Output Bin, Integrated Duplex, Single-Sheet Manual Feed

Optional Paper Handling

550-Sheet Tray, 650-Sheet Duo Tray

Paper Input Capacity, Standard

Do 250+1 strani 20 lbs ali 75 g bond

Paper Input Capacity, Maximum

Do 1450+1 strani 20 lbs ali 75 g bond

Paper Output Capacity, Standard

Do 125 strani 20 lbs ali 75 g bond

Paper Output Capacity, Maximum

Do 125 strani 20 lbs ali 75 g bond

Paper Weight Range Supported - Standard Tray (gsm)

60 - 200 gsm

Integrated Tray Card Stock Upper limit (grain long)

Cover - 216 gsm (74 lb), Index Bristol - 200 gsm (110 lb), Tag -200 gsm (122 lb)

Finishing Option

No

Number of Paper Inputs, Standard

2

Number of Paper Inputs, Maximum

5

Media Types Supported

Card Stock, Envelopes, Paper Labels, Plain Paper, Vinyl Labels, Refer to the Paper & Specialty Media Guide

Media Sizes Supported

10 Envelope, 7 3/4 Envelope, 9 Envelope, A4, A5, B5 Envelope, C5 Envelope, DL Envelope, Hagaki Card, Executive, Folio, JIS-B5, Legal, Letter, Statement, Universal, Oficio, A6

Standard Connectivity

USB 2.0 Specification Hi-Speed Certified (Type B), Gigabit Ethernet (10/100/1000), Front USB 2.0 Specification Hi-Speed Certified port (Type A)

Optional Network Ports

Marknet N8372 WiFi Option

Direct USB

Yes

Ethernet Network

Yes

Network Protocol Support

TCP/IP IPv4, TCP/IP IPv6, TCP, UDP

Načini mrežnega tiskanja

LPR/LPD, Direct IP (Port 9100), Enhanced IP (Port 9400), FTP, TFTP, ThinPrint .print integration, Telnet, IPP 1.0, 1.1, 2.0 (Internet Printing Protocol)

Network Management Protocols¹

HTTP, HTTPS (SSL/TLS), SNMPv1, SNMPv2c, SNMPv3, WINS, IGMP, APIPA (AutoIP), DHCP, ICMP, DNS, Bonjour, DDNS, mDNS, ARP, NTP, Telnet, Finger,

Network Security

SNMPv3, 802.1x Authentication: MD5, MSCHAPv2, LEAP, PEAP, TLS, TTLS, IPSec

Printable Area (metric)

4.2 mm zgornjih, spodnjih, desni in levih robov (znotraj)

Printer Languages (Standard)

PCL 5c Emulation, PCL 6 Emulation, Personal Printer Data Stream (PPDS), PostScript 3 Emulation, Direct Image, Microsoft XPS (XML Paper Specification), AirPrint™, PDF 1.7 emulation

Fonts and Symbol Sets

3 of 9 scalable PCL 5e fonts in Narrow, Regular and Wide, 158 scalable PostScript fonts, 2 PCL bitmap fonts, 39 scalable PPDS fonts, 5 PPDS bitmap fonts, 84 scalable PCL fonts, OCR-A, OCR-B scalable PCL 5e fonts, For more information, refer to the Technical Reference.

Laser Cartridge Yields (up to)⁵

, 1,400-page Colour (CMY) Cartridges, 2,000-page Black Cartridge, 5,000-page Colour (CMY) Extra High Yield Cartridges, 8,500-page Black Extra High Yield Cartridge, 7,000-page Colour (CMY) Ultra High Yield Cartridges, 10,500-page Black Ultra High Yield Cartridge

Photoconductor Estimated Yield

Do 125,000 pages, based on 3 average letter/A4-size pages per print job and ~ 5% coverage⁴

Cartridge(s) Shipping with Product

2,000-page Colour (CMY) Return Program Toner Cartridges, 3,000-page Black Return Program Toner Cartridge

Replacement Cartridges:

Product functions only with replacement cartridges designed for use in a specific geographical region. See www.lexmark.com/ regions for more details.

Packaged Size (mm - H x W x D)

402 x 495 x 595 mm

Packaged Weight, kg

23.9 kg

Size (mm - H x W x D)

308 x 442 x 421 mm

Weight

21 kg

Noise level (Idle mode)

Inaudible dBA

Noise Level (Print), Operating

51 dBA

Duplex Print Noise Level, Operating

53 dBA

Quiet Mode

47 dBA

ENERGY STAR

Yes

Average Power (Hibernate Mode)

0.2 watts

Average Power (Sleep Mode)

1.42 watts

Average Power (Ready Mode)

37 watts

Average Power (Printing)

570 watts

Average Power while Printing Duplex

380 watts

ENERGY STAR Typical Electricity**Consumption (TEC)**

0.57 kilowatt-hours per week

Garancija izdelka

1-Year Onsite Repair, Next Business Day

Product Certifications

ENERGY STAR, Blue Angel RAL-UZ 205, ICES-003 Class A, BSMI Class A, VCCI Class A, US FDA, UL 60950-1, FCC Class A, cUL CAN/CSA-C22.2 60950-1, CB EN/IEC 60950-1, CB EN/IEC 60825-1, CE DoC (EN 62301 Class A, EN 62311, CE EN/IEC 60950-1, CE EN/IEC 60825-1, EN 61000-3, EN 55022 Class A, EN 55024, UL), EFTA (CE), KCC, CCC, CECF, CEL, C-tick DoC, UL-AR, KC mark, UL GS mark, UCRF, EC 1275, China Green Product (CGP)

Maximum Monthly Duty CycleDo 100000 Strani na mesec³**Recommended Monthly Page Volume**1500 - 10000 Strani²**Specified Operating Environment**

Humidity: 8 to 80% Relative Humidity, Altitude: 0 - 3048 Meters (10,000 Feet), Temperature: 10 to 32°C (50 to 90°F)

License/Agreement Terms

Printers are sold subject to certain license/agreement conditions. See www.lexmark.com/printerlicense for details.

Country of Origin

China (PRC)

UNSPSC Code

43212105

¹This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (<http://www.openssl.org/>)

²"Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage.

³"Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs.

⁴Actual Yield may vary based on other factors such as device speed, paper size and feed orientation, toner coverage, tray source, percentage of black-only printing and average print job complexity.

⁵Average continuous black or continuous composite CMY declared cartridge yield up to this number of standard pages in accordance with ISO/IEC 19798.

⁶Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds.



Callout	Availability	Description
1	Standard	4.3-inch (10.9-cm) Touch Screen
2	Dodatno	650-Sheet Duo Tray
3	Dodatno	Keyboard
4	Dodatno	550-Sheet Tray

P/N	Kartuše z barvilom	P/N	Pohištvo
78C50C0	Lexmark 78C10C0 Cyan Return Programme Toner Cartridge	40C2300	Adjustable Stand
78C0ZK0	Lexmark 78C0ZK0 Black Return Programme Imaging Kit	P/N	Možnosti pomnilnika
78C0ZV0	Lexmark 78C0ZV0 Black and Color Return Programme Imaging Kit	57X9801	256MB Flash Memory Card
78C0Z10	Lexmark 78C0Z10 Black Imaging Kit	57X9814	Korean Font Card
78C0Z50	Lexmark 78C0Z50 Black and Colour Imaging Kit	57X9815	Japanese Font Card
78C0W00	Lexmark 78C0W00 Waste Toner Bottle	57X9812	Simplified Chinese Font Card
78C50M0	Lexmark 78C10M0 Magenta Return Programme Toner Cartridge	57X9810	Traditional Chinese Font Card
78C50Y0	Lexmark 78C10Y0 Yellow Return Programme Toner Cartridge	27X0805	500+ GB Hard Disk
78C50K0	Lexmark 78C10K0 Black Return Programme Toner Cartridge	P/N	Programske rešitve
78C5XC0	Lexmark 78C1XC0 Cyan Extra High Yield Return Programme Toner Cartridge	40C9200	Forms and Bar Code Card
78C5XM0	Lexmark 78C1XM0 Magenta Extra High Yield Return Programme Toner Cartridge	40C9202	Card for PRESCRIBE Emulation
78C5XY0	Lexmark 78C1XY0 Yellow Extra High Yield Return Programme Toner Cartridge	57X0300	Contact Authentication Device
78C5XK0	Lexmark 78C1XK0 Black Extra High Yield Return Programme Toner Cartridge	57X0301	Contactless Authentication Device
78C5UC0	Lexmark 78C1UC0 Cyan Ultra High Yield Return Programme Toner Cartridge	57X0210	Elatec Reader Authentication Device
78C5UM0	Lexmark 78C1UM0 Magenta Ultra High Yield Return Programme Toner Cartridge	57X0250	Elatec TWN4 MultiTech-P LEGIC 42 Kit Bosch-SPR000264
78C5UY0	Lexmark 78C1UY0 Yellow Ultra High Yield Return Programme Toner Cartridge	P/N	Možnosti povezovanja
78C5UK0	Lexmark 78C1UK0 Black Ultra High Yield Return Programme Toner Cartridge	27X6410	Lexmark MarkNet N8372 802.11 a/b/g/n/ac Wireless Print Server
78C0U20	Lexmark 78C0U20 Cyan Ultra High Yield Toner Cartridge	57X7040	English Keyboard Kit
78C0U30	Lexmark 78C0U30 Magenta Ultra High Yield Toner Cartridge	SPD0002	Surge Protective Device, 220-240V
78C0U40	Lexmark 78C0U40 Yellow Ultra High Yield Toner Cartridge	P/N	Podaljšane garancije
78C0U10	Lexmark 78C0U10 Black Ultra High Yield Toner Cartridge	2364027	CS622 2-Years Total (1+1) Onsite Service
78C50CE	Lexmark 78C10CE Cyan Contract Toner Cartridge	2364028	CS622 3-Years Total (1+2) Onsite Service
78C50ME	Lexmark 78C10ME Magenta Contract Toner Cartridge	2364029	CS622 4-Years Total (1+3) Onsite Service
78C50YE	Lexmark 78C10YE Yellow Contract Toner Cartridge	2364030	CS622 5-Years Total (1+4) Onsite Service
78C50KE	Lexmark 78C10KE Black Contract Toner Cartridge	2364031	CS622 1-Year Onsite Service Renewal
78C5XCE	Lexmark 78C1XCE Cyan Extra High Yield Contract Toner Cartridge	2364032	CS622 1-Year Post Wty Onsite Repair NBD Warranty
78C5XME	Lexmark 78C1XME Magenta Extra High Yield Contract Toner Cartridge	2365034	CS622 6-Years Total (1+5) Onsite Service
78C5XYE	Lexmark 78C1XYE Yellow Extra High Yield Contract Toner Cartridge	2367194	CS622 7-Years Total (1+6) Onsite Service
78C5XKE	Lexmark 78C1XKE Black Extra High Yield Contract Toner Cartridge	2365035	CS622 2-Year Onsite Service Renewal
78C5UCE	Lexmark 78C1UCE Cyan Ultra High Yield Contract Toner Cartridge	2365036	CS622 3-Year Onsite Service Renewal
78C5UME	Lexmark 78C1UME Magenta Ultra High Yield Contract Toner Cartridge	2365037	CS622 4-Year Onsite Service Renewal
78C5UYE	Lexmark 78C1UYE Yellow Ultra High Yield Contract Toner Cartridge		
78C5UKE	Lexmark 78C1UKE Black Ultra High Yield Contract Toner Cartridge		
P/N	Ravnanje s papirjem		
42C7550	550-Sheet Tray		
42C7650	650-sheet Duo Tray		