



Lexmark MC2535adwe

The multi-function Lexmark MC2535adwe builds on colour output of up to 35 [33] pages per minute* with a 4.3-inch [10.9-cm] colour touch screen.

Part Number

42CC460

Print Technology

Color Laser

Function

Color Copying, Color Faxing, Color Printing, Color Scanning

Workgroup Size

Small-Medium Workgroup

Touch Screen Display

Yes

Display

Lexmark e-Task 4.3-inch (10.9 cm) colour touch screen

Print Speed (Letter, Black)

Up to 35 ppm⁵

Print Speed (Letter, Colour)

Up to 35 ppm⁵

Print Speed (Letter, Black) Duplex

Up to 17.5 spm⁵

Print Speed (Letter, Colour) Duplex

Up to 17.5 spm⁵

Print Speed (A4, Black)

Up to 33 ppm⁵

Print Speed (A4, Colour)

Up to 33 ppm⁵

Print Speed (A4, Black) Duplex

Up to 16 spm⁵

Print Speed (A4, Colour) Duplex

Up to 16 spm⁵

Time to First Page (Black)

As fast as <8.5 seconds

Time to First Page (Colour)

As fast as <8.5 seconds

Duplex (2-sided) Printing

Integrated Duplex

Print Resolution, Black

1200 x 1200 dpi, 4800 Color Quality (2400 x 600 dpi)

Print Resolution, Colour

1200 x 1200 dpi, 4800 Color Quality (2400 x 600 dpi)

Copy Speed (Letter, Black)

Up to 35 cpm⁵

Copy Speed (Letter, Colour)

Up to 35 cpm⁵

Copy Speed (Letter, Black) Duplex

Up to 17.5 spm⁵

Copy Speed (Letter, Colour) Duplex

Up to 17.5 spm⁵

Copy Speed (A4, Black)

Up to 33 cpm⁵

Copy Speed (A4, Colour)

Up to 33 cpm⁵

Copy Speed (A4, Black) Duplex

Up to 16 spm⁵

Copy Speed (A4, Colour) Duplex

Up to 16 spm⁵

Time to First Copy (Black)

As fast as 9 seconds

Time to First Copy (Colour)

As fast as 9.5 seconds

Reduce / Enlarge Range

25 - 400 %

A4/Ltr Simplex Scan Speed (Black)

Up to 47 / 50 sides per minute

A4/Ltr Simplex Scan Speed (Colour)

Up to 30 / 32 sides per minute

A4/Ltr Duplex Scan Speed (Black)

Up to 21 / 23 sides per minute

A4/Ltr Duplex Scan Speed (Colour)

Up to 13 / 14 sides per minute

Scan Area, Maximum (mm)

215.9 x 355.6 mm

ADF Scan

RADF (reversing Duplex)

Scanner Type

Flatbed scanner with ADF

Scan Technology

CIS

Optical Scanning Resolution

up to 600 X 600 ppi (color), up to 1200 X 600 ppi (black)

Scan File Formats (Send as)

JPEG, JPG, PDF, Secure PDF, TIFF, XPS, BMP, Archival PDF (A-1a, A-1b), Searchable PDF (optional OCR with 1GB RAM and hard disk required), Highly compressed PDF (1GB RAM and hard disk required)

Scan Destinations

e-mail, FTP, USB Flash drive, USB or Network connected computer, Lexmark Document Solutions Suite (LDSS)

Modem Speed

Max is 33,600 bps, V.34 Half-Duplex Kbps

Fax Transmission Speed

< 3 seconds per page

Processor

Quad Core, 1200 w/ GPU MHz

Memory, Standard

2048 MB

Memory, Maximum

6144 MB

Hard Disk

Option available

Apple Operating Systems Supported

Apple OS X (10.6, 10.7, 10.8, 10.9, 10.10, 10.11, 10.12, 10.13)

Citrix MetaFrame

Microsoft Windows 2000 Server running Terminal Services with Citrix MetaFrame XP Presentation Server or Citrix MetaFrame Presentation Server 3.0., Microsoft Windows 2000 Server running Terminal Services with Citrix Presentation Server 4.0, Microsoft Windows 2000 Server running Terminal Services with Citrix Presentation Server 3.0, 4.0, Microsoft Windows Server 2012 with Citrix XenApp 6.0, 6.5

Linux Operating Systems Supported

Debian GNU/Linux 7.0, 8.0, SUSE Linux Enterprise Server 10, 11, 12, openSUSE Linux 13.2, Ubuntu 16.04 LTS, Fedora 23, 24, Red Hat Enterprise Linux WS 6, 7, openSUSE Linux 42.3

Microsoft Windows Operating Systems Supported

Windows 7, Windows 7 x64, Windows 8, Windows 8 x64, Windows 8.1, Windows 8.1 x64, Windows 10

Novell Operating Systems Supported

Novell NetWare 6.5 Open Enterprise Server, Novell NetWare 5.1(SP 6+), 6.0(SP 3+) with Novell Distributed Print Services (NDPS), Novell Open Enterprise Server on SUSE Linux Enterprise Server, Novell Open Enterprise Server 2 on SUSE Linux Enterprise Server 10 SP4, Novell Open Enterprise Server 11 on SUSE Linux Enterprise Server 11, Novell Open Enterprise Server 2 SP2 on SuSE Linux Enterprise Server 10 SP3 3

UNIX Operating Systems Supported

Sun Solaris x86 10, 11, Sun Solaris SPARC 10, 11, IBM AIX 6.1, 7.1

Included Paper Handling

250-Sheet Input, 150-Sheet Output Bin, Integrated Duplex, Single-Sheet Manual Feed

Optional Paper Handling

550-Sheet Tray, 650-Sheet Duo Tray

Paper Input Capacity, Standard

Up to 250+1 pages 20 lb or 75 gsm bond

Paper Input Capacity, Maximum

Up to 1450+1 pages 20 lb or 75 gsm bond

Paper Output Capacity, Standard

Up to 150 pages 20 lb or 75 gsm bond

Paper Output Capacity, Maximum

Up to 150 pages 20 lb or 75 gsm bond

Paper Weight Range Supported - Standard Tray (gsm)

90.3 - 105 gsm

Integrated Tray Card Stock Upper limit (grain long)

Cover - 200 gsm (74 lb), Index Bristol - 200 gsm (110 lb), Tag -200 gsm (122 lb)

ADF

50-Sheet Automatic Document Feeder

ADF Paper Input Capacity

Up to 50 pages 20 lb or 75 gsm bond

ADF Paper Output Capacity

Up to 50 pages 20 lb or 75 gsm bond

Finishing Option

No

Number of Paper Inputs, Standard

2

Number of Paper Inputs, Maximum

5

Media Types Supported

Card Stock, Paper Labels, Plain Paper, Vinyl Labels, Refer to the Paper & Specialty Media Guide

Media Sizes Supported

10 Envelope, 7 3/4 Envelope, A4, A5, B5 Envelope, C5 Envelope, DL Envelope, Hagaki Card, Executive, Folio, JIS-B5, Legal, Letter, Universal, Oficio, A6

Standard Ports

USB 2.0 Specification Hi-Speed Certified (Type B), Gigabit Ethernet (10/100/1000), 802.11b/g/n Wireless, Front USB 2.0 Specification Hi-Speed Certified port (Type A)

Optional Network Ports

Marknet N8372 WiFi Option

Direct USB

Yes

Ethernet Network

Yes

Wireless

Yes

Network Protocol Support

TCP/IP IPv4, AppleTalk™, TCP/IP IPv6, TCP, UDP

Network Printing Methods

LPR/LPD, Direct IP (Port 9100), Enhanced IP (Port 9400), FTP, TFTP, ThinPrint .print integration, Telnet, IPP 1.0, 1.1, 2.0 (Internet Printing Protocol), Microsoft Web Services WSD, Pull Printing

Network Management Protocols¹

HTTP, HTTPS (SSL/TLS), SNMPv1, SNMPv2c, SNMPv3, WINS, IGMP, BOOTP, RARP, APIPA (AutoIP), DHCP, ICMP, DNS, Bonjour, DDNS, mDNS, ARP, NTP, Telnet, Finger,

Network Security

SNMPv3, 802.1x Authentication: MD5, MSCHAPv2, LEAP, PEAP, TLS, TTLS, IPsec

Printable Area (metric)

4.2 mm of the top, bottom, right and left edges (within)

Printer Languages (Standard)

PCL 5c Emulation, PCL 6 Emulation, Personal Printer Data Stream (PPDS), PostScript 3 Emulation, Direct Image, Microsoft XPS (XML Paper Specification), AirPrint™, PDF 1.7 emulation

Fonts and Symbol Sets

3 of 9 scalable PCL 5e fonts in Narrow, Regular and Wide, 158 scalable PostScript fonts, 2 PCL bitmap fonts, 39 scalable PPDS fonts, 5 PPDS bitmap fonts, 84 scalable PCL fonts, OCR-A, OCR-B scalable PCL 5e fonts, For more information, refer to the Technical Reference.

Laser Cartridge Yields (up to)

1,000-page Black and Colour (CMYK) Cartridges, 6,000-page Black Extra High Yield Cartridge, Average continuous cartridge yield is stated number of standard pages as listed. Declared yield value in accordance with ISO/IEC 19798., 2,300-page Colour (CMY) High Yield Cartridges, 3,000-page Black High Yield Cartridge, 3,500-page Colour (CMY) Extra High Yield Cartridges, 8,000-page Black Ultra High Yield Cartridge

Photoconductor Estimated Yield

Up to 125000 pages, based on 3 average letter/A4-size pages per print job and ~ 5% coverage⁴

Cartridge(s) Shipping with Product

1,400-page Color (CMY) Starter Return Program Toner Cartridge, 3,000-page Black Starter Return Program Toner Cartridge

Replacement Cartridges:

Product functions only with replacement cartridges designed for use in a specific geographical region. See www.lexmark.com/ regions for more details.

Packaged Size (mm - H x W x D)

570 x 558 x 594 mm

Packaged Weight, kg

30.8 kg

Size (mm - H x W x D)

462 x 442 x 588 mm

Weight

27.1 kg

Noise Level, Idle

Inaudible dBA

Noise Level (Print), Operating

52 dBA

Duplex Print Noise Level, Operating

53 dBA

Noise Level (Copy), Operating

56 dBA

Noise Level (Scan), Operating

55 dBA

ENERGY STAR

Yes

Limited Warranty - See Statement of Limited Warranty

1-Year Onsite Service, Next Business Day

Product Certifications

ENERGY STAR, Blue Angel RAL-UZ-171, ICES-003 Class B, BSMI Class B, VCCI Class B, US FDA, UL 60950-1, FCC Class B, cUL CAN/CSA-C22.2 60950-1, CB EN/IEC 60950-1, CB EN/IEC 60825-1, CE DoC (EN 62301 Class B, EN 62311, CE EN/IEC 60950-1, CE EN/IEC 60825-1, EN 61000-3, EN 55022 Class B, EN 55024, UL), EFTA (CE), KCC, CCC, CECP, CEL, C-tick DoC, UL-AR, KC mark, UL GS mark, EC 1275, MET-I, ISO 532B, ECMA-370, GOST-R, SIL, TER

Maximum Monthly Duty Cycle

Up to 85000 pages per month³

Recommended Monthly Page Volume

1500 - 8500 pages²

Specified Operating Environment

Humidity: 8 to 80% Relative Humidity, Altitude: 0 - 3048 meters, Temperature: 10 to 32°C (50 to 90°F)

License/Agreement Terms

Printers are sold subject to certain license/agreement conditions. See www.lexmark.com/ printerlicense for details.

Country of Origin

China (PRC)

UNSPSC Code

43212110

Harmonized Tariff Code

8443.31.0000

¹This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (<http://www.openssl.org/>)

²"Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage.

³"Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs.

⁴Actual Yield may vary based on other factors such as device speed, paper size and feed orientation, toner coverage, tray source, percentage of black-only printing and average print job complexity.

⁵Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds.

P/N	Toner Cartridges
78COZK0	Lexmark 78COZK0 Black Return Program Imaging Kit
78COZV0	Lexmark 78COZV0 Black and Colour Return Program Imaging Kit
78COZ10	Lexmark 78COZ10 Black Imaging Kit
78COZ50	Lexmark 78COZ50 Black and Colour Imaging Kit
78COW00	Lexmark 78COW00 Waste Toner Bottle
78COD10	Lexmark 78COD10 Black Developer Unit
78COD20	Lexmark 78COD20 Cyan Developer Unit
78COD30	Lexmark 78COD30 Magenta Developer Unit
78COD40	Lexmark 78COD40 Yellow Developer Unit
C2310C0	Lexmark C2310C0 Cyan Return Program Toner Cartridge
C2310M0	Lexmark C2310M0 Magenta Return Program Toner Cartridge
C2310Y0	Lexmark C2310Y0 Yellow Return Program Toner Cartridge
C2310K0	Lexmark C2310K0 Black Return Program Toner Cartridge
C231HC0	Lexmark C231HC0 Cyan High-Yield Return Program Toner Cartridge
C231HM0	Lexmark C231HM0 Magenta High-Yield Return Program Toner Cartridge
C231HY0	Lexmark C231HY0 Yellow High-Yield Return Program Toner Cartridge
C231HK0	Lexmark C231HK0 Black High-Yield Return Program Toner Cartridge
C241XC0	Lexmark C241XC0 Cyan Extra-High-Yield Return Program Toner Cartridge
C241XK0	Lexmark C241XK0 Black Extra-High-Yield Return Program Toner Cartridge
C241XM0	Lexmark C241XM0 Magenta Extra-High-Yield Return Program Toner Cartridge
C241XY0	Lexmark C241XY0 Yellow Extra-High-Yield Return Program Toner Cartridge
C240X20	Lexmark C240X20 Cyan Extra-High-Yield Toner Cartridge
C240X30	Lexmark C240X30 Magenta Extra-High-Yield Toner Cartridge
C240X40	Lexmark C240X40 Yellow Extra-High-Yield Toner Cartridge
C251UK0	Lexmark C251UK0 Black Ultra-High-Yield Return Program Toner Cartridge
C250U10	Lexmark C250U10 Black Ultra-High-Yield Toner Cartridge

P/N	Paper Handling
42C7550	550-Sheet Tray
42C7650	650-sheet Duo Tray

P/N	Furniture
3073173	Swivel Cabinet
35S8502	Adjustable Stand

P/N	Memory Options
27X0400	500+ GB Hard Disk
57X9801	256MB Flash Memory Card
57X9814	Korean Font Card
57X9815	Japanese Font Card
57X9812	Simplified Chinese Font Card
57X9810	Traditional Chinese Font Card

P/N	Memory Options
57X0204	4GBx32 DDR3-DRAM

P/N	Application Solutions
40C9200	Forms and Bar Code Card
40C9202	Card for PRESCRIBE Emulation

P/N	Connectivity
27X6410	Lexmark MarkNet N8372 802.11 a/b/g/n/ac Wireless Print Server
1021294	USB (2 Meter) Cable
SPD0001	Surge Protective Device, 110-120V

P/N	Extended Warranties
2364341	MC2535 2 Year Base Warranty Onsite Repair NBD Warranty
2364340	MC2535 1 Year Base Warranty Onsite Repair NBD Warranty
2364342	MC2535 2-Years Total (1+1) Onsite Service
2364343	MC2535 3-Years Total (1+2) Onsite Service
2364344	MC2535 4-Years Total (1+3) Onsite Service
2364345	MC2535 5-Years Total (1+4) Onsite Service
2364346	MC2535 1-Year Onsite Service Renewal
2364347	MC2535 1-Year Post Wty Onsite Repair NBD Warranty
2364348	MC2535 Per Call 1-Time Onsite Repair NBD Warranty
2364354	MC2535 Upgrade to Onsite Service
2364355	MC2535 Upgrade to 2 Year Onsite Service
2364356	MC2535 2 Year Upgrade to Onsite Service
2364357	MC2535 3 Year Upgrade to Onsite Service

P/N	User Replaceable Parts
41X0917	ADF Separator Roll