



Lexmark CX730de

The Lexmark CX730de is designed for performance, security and ease of use for mid-to-large workgroups at speeds of up to 40 pages per minute*.

Part Number

47C9520

Print technology

Colour Laser

Functionality

Colour Copying, Colour Printing, Colour Scanning, Colour Network Scanning, Trusted Platform Module (TPM), The Trusted Platform Module (TPM) is not available in some countries.

Workgroup size

Medium-Large Workgroup

Touch screen display

Yes

Display

Lexmark e-Task 17,8 cm colour touch screen with audible feedback

Print speed (A4, black)

Up to 40 ppm⁶

Print speed (A4, colour)

Up to 40 ppm⁶

Print speed (A4, black) duplex

Up to 30.5 spm⁶

Time to first page (black)

As fast as 6.4 seconds

Time to first page (colour)

As fast as 7.0 seconds

Duplex (2-sided) printing

Integrated Duplex

Print resolution, black

1200 x 1200 dpi, 4800 CQ (2400 x 600 dpi)

Print resolution, colour

1200 x 1200 dpi, 4800 CQ (2400 x 600 dpi)

Copy speed (A4, black)

Up to 39.5 cpm⁶

Copy speed (A4, colour)

Up to 39.5 cpm⁶

Time to first copy (black)

As fast as 6.7 seconds

Time to first copy (colour)

As fast as 7.3 seconds

Reduce / enlarge range

25 - 400 %

Simplex scan speed (A4, black)

Up to 40 / 42 spm

Simplex scan speed (A4, colour)

Up to 40 / 42 spm

Duplex scan speed (A4, black)

Up to 80 / 84 spm

Duplex scan speed (A4, colour)

Up to 80 / 84 spm

Scan area, maximum

216 x 356 mm

ADF scan

DADF (single pass Duplex)

Scanner type

Flatbed scanner with ADF

Scan technology

Trilinear CIS

Scan resolution, enhanced

Up to 600 X 600 dpi

Scan resolution, optical

Up to 600 dpi

Scan file formats (send as)

JPEG, JPG, PDF, Secure PDF, TIFF, Archival PDF (A-1a, A-1b), Searchable PDF (optional OCR with 1GB RAM and hard disk required), Highly compressed PDF (1GB RAM and hard disk required)

Scan destinations

e-mail, FTP, USB Flash drive, USB or Network connected computer, Lexmark Document Solutions Suite (LDSS)

Processor speed

Quad Core 1.2 GHz

Memory, standard

2048 MB

Memory, maximum

2048 MB

Hard Disk

Intelligent Storage Drive available; Magnetic Hard Disk available

Apple Operating Systems Supported

Support is provided through AirPrint and AirScan only

Citrix MetaFrame

Microsoft Windows Server 2008 and 2008 X64 Edition with Citrix XenApp 5.0, Microsoft Windows Server 2008 R2 with Citrix XenApp 6.0, 6.5, Microsoft Windows Server 2012 with Citrix XenApp 6.0, 6.5

Linux operating systems supported

Debian GNU/Linux 7.0, 8.0, Fedora 21, 22, Linpus Linux Lite Desktop 2.1, Linux Mint 13 LTS, 17 LTS, 17.1 LTS, 17.2 LTS, Linux Mint 2 Debian, PCLinuxOS 2014.12, Red Hat Enterprise Linux WS 4, 5, 6, 7, SUSE Linux Enterprise Desktop 10, 11, 12, SUSE Linux Enterprise Server 10, 11, 12, Ubuntu 12.04 LTS, 14.04 LTS, 15.04, openSUSE 13.1, 13.2, openSUSE Tumbleweed

Microsoft Windows operating systems supported

Windows XP, Windows XP x64, Windows Vista, Windows Vista x64, Windows Server 2008, Windows Server 2008 x64, Windows 7, Windows 7 x64, Windows Server 2008 R2, Windows 8, Windows 8 x64, Windows Server 2012, Windows 8.1, Windows 8.1 x64, Windows Server 2012 R2, Windows RT, Windows RT 8.1, Windows 10, Windows 11

Novell operating systems supported

Novell NetWare 6.5 Open Enterprise Server, Novell Open Enterprise Server 2 on SUSE Linux Enterprise Server 10 SP4, Novell Open Enterprise Server 11 on SUSE Linux Enterprise Server 11

UNIX operating systems supported

Sun Solaris x86 10, 11, Sun Solaris SPARC 10, 11, IBM AIX 6.1, 7.1

Standard paper handling

550-Sheet Input, 100-Sheet Multipurpose Feeder, Integrated Duplex, 300-sheet output bin

Optional paper handling

550-Sheet Tray

Paper input capacity, standard

Up to 650 pages

Paper input capacity, maximum

Up to 2850 pages

Paper output capacity, standard

Up to 300 pages

Paper output capacity, maximum

Up to 300 pages

Paper weight range supported - standard tray

60 - 218 g/m²

Paper weight range supported - multipurpose feeder

60 - 218 g/m²

Integrated Tray Card Stock Upper limit (grain long)

Index Bristol - 199 g/m², Tag - 163 g/m², Cover - 176 g/m²

Integrated Tray Card Stock Upper limit (grain short)

Index Bristol - 199 gsm (110 lb), Cover - 216 g/m², Tag - 203 gsm (125 lb)

Autom. document feeder (ADF)

100-Sheet Automatic Document Feeder

ADF paper input capacity

Up to 100 pages

ADF paper output capacity

Up to 100 pages

Finishing

No

Number of paper inputs, standard

2

Number of paper inputs, maximum

6

Media types supported

Card Stock, Envelopes, Paper Labels, Plain Paper, Vinyl Labels, Banner Paper, Refer to the Paper & Specialty Media Guide

Media sizes supported

10 Envelope, 7 3/4 Envelope, 9 Envelope, A4, A5, B5 Envelope, C5 Envelope, DL Envelope, Executive, Folio, JIS-B5, Legal, Letter, Statement, Universal, Oficio, A6

Caster base

No

Standard connectivity

One Internal Card Slot, USB 2.0 Specification Hi-Speed Certified (Type B), Gigabit Ethernet (10/100/1000), Front USB 2.0 Specification Hi-Speed Certified port (Type A), Rear Hi-Speed USB port (compatible with USB 2.0 specification, type A)

Optional network ports

Internal MarkNet N8370 802.11b/g/n/a
Wireless, NFC

Direct USB

Yes

Ethernet network

Yes

Wireless

Wireless Option

Network protocol support

TCP/IP IPv4, TCP/IP IPv6, TCP, UDP, IPSEC w/ IPv4, IPSEC w/ IPv6, ICMP, IGMP

Network printing methods

LPR/LPD, Direct IP (Port 9100), Enhanced IP (Port 9400), Secure IP (Port 96xx), FTP, ThinPrint .print integration, IPP 1.0, 1.1, 2.0 (Internet Printing Protocol), Microsoft Web Services WSD, Pull Printing

Network management protocols¹

HTTP, HTTPs (SSL/TLS), SNMPv1, SNMPv2c, SNMPv3, WINS, IGMP, BOOTP, RARP, APIPA (AutoIP), DHCP, ICMP, DNS, DDNS, mDNS, ARP, NTP, Telnet, Finger,

Network security

SNMPv3, 802.1x Authentication: MD5, MSCHAPv2, LEAP, PEAP, TLS, TTLS, Certificate Management, SSL Cipher Configuration, TCP/UDP Port Access Control, Security Port Lockdown, IPSEC Support (IPv4/IPv6)

Printable area

4.2 mm of the top, bottom, right and left edges (within)

Printer languages (standard)

PCL 6 Emulation, Personal Printer Data Stream (PPDS), PostScript 3 Emulation, Direct Image, PDF 1.7 emulation, PCL 5

Fonts and symbol sets

158 scalable PostScript fonts, 39 scalable PPDS fonts, 5 PPDS bitmap fonts, For more information, refer to the Technical Reference., 89 scalable PCL 6 fonts, 2 PCL 6 bitmap fonts

Cartridge yields: up to⁵

, 22,000-page Black High Yield Cartridge, 10,500-page Colour (CMY) High Yield Cartridges

Imaging unit yield

Up to 150000 pages, based on average 3 pages per print job and 5% coverage⁴

Cartridge(s) shipped with product

5,000-page (CMYK) Return Programme Toner Cartridges

Replacement cartridges:

Product functions only with replacement cartridges designed for use in a specific geographical region. See www.lexmark.com/ regions for more details.

Packaged size (HxWxD)

838 x 700 x 735 mm

Packaged weight

52.5 kg

Size (HxWxD)

621 x 479 x 533 mm

Weight

39 kg

Noise level, idle

14 dBA

Noise Level (Print), Operating

52 dBA

Duplex print noise level, operating

53 dBA

Noise Level (Copy), Operating

55 dBA

Noise Level (Scan), Operating

51 dBA

Quiet mode

47 dBA

Energy Star

Yes

Average power in Hibernate mode

0.1 Watt

Average power in Sleep mode

1 Watt

Average power in Ready mode

61 Watt

Average power while printing

630 Watt

Average power while printing duplex

520 Watt

Average power while copying

640 Watt

Average power while scanning

44.5 Watt

Energy Star Typical Electricity Consumption (TEC)

0.55 kWh per week

Product guarantee

1-Year Onsite Service, Next Business Day

Product certifications

ENERGY STAR, ICES-003 Class A, BSMI Class A, VCCI Class A, FCC Class A, NOM-032, UL, cUL, NOM, US FDA/CDRH, IEC 60825-1, CB Report, ISO-532B, CE (EU) DoC, EFTA (CE), KC logo, CCC, C-tick DoC, EuP, CECP, CEL, EC 1275/2008, ECMA-370, TED, SII, TER, SABS, UL-AR, GS Mark, Green Dot, ISO-9296, COC, EPEAT, China Green Product (CGP), Mopria Certified, Blue Angel / RAL-UZ 219

Maximum monthly duty cycle

Up to 120000 pages per month³

Recommended monthly page volume

1500 - 15000 pages²

Specified operating environment

Humidity: 8 to 80% Relative Humidity, Temperature: 10 to 32°C (50 to 90°F), Altitude: 0 - 2896 Metres (9,500 Feet)

License/Agreement Terms

Printers are sold subject to certain license/ agreement conditions. See www.lexmark.com/ printerlicense for details.

Country of origin

China (PRC), Mexico

UNSPSC code

43212110

¹This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (<http://www.openssl.org/>)

²"Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range

for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage.

³"Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs.

⁴Actual Yield may vary based on other factors such as device speed, paper size and feed orientation, toner coverage, tray source, percentage of black-only printing and average print job complexity.

⁵Average continuous black or continuous composite CMY declared cartridge yield up to this number of standard pages in accordance with ISO/IEC 19798.

⁶Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds.



8



1



2



| P/N | Toner Cartridges | P/N | Extended Warranties |
|---------|--|---------|---|
| 71C0Z10 | Lexmark CS/CX730, 735, C/XC4342, C/XC4352 Black 150K Imaging Unit | 2372863 | CX730 5 Year Onsite Repair NBD Warranty |
| 71C0Z50 | Lexmark CS/CX730, 735, C/XC4342, C/XC4352 Colour (CMY) 150K Imaging Unit | 2372864 | CX730 6 Year Onsite Repair NBD Warranty |
| 71C0W00 | Lexmark CS/CX730, 735, C/XC4342, C4352 170K Waste Container | 2372865 | CX730 1 Year Renewal Onsite Repair, Response Time Next Business Day |
| 71C0H20 | Lexmark CS/CX730 Cyan 10.5K Toner Cartridge | 2372866 | CX730 2 Year Renewal Onsite Repair, Response Time Next Business Day |
| 71C0H30 | Lexmark CS/CX730 Magenta 10.5K Toner Cartridge | 2372867 | CX730 3 Year Renewal Onsite Repair, Response Time Next Business Day |
| 71C0H40 | Lexmark CS/CX730 Yellow 10.5K Toner Cartridge | 2372868 | CX730 4 Year Renewal Onsite Repair, Response Time Next Business Day |
| 71C0H10 | Lexmark CS730, 735, CX730 Black 22K Toner Cartridge | 2372869 | CX730 1 Year Post Warranty Onsite Repair Next Business Day |
| 71C20C0 | Lexmark CS/CX730, 735 Cyan Return Programme 5K Toner Cartridge | 2372870 | CX730 Per Call Onsite Repair Next Business Day Warranty |
| 71C20M0 | Lexmark CS/CX730, 735 Magenta Return Programme 5K Toner Cartridge | 2372884 | CX730 1 Year Parts Only Extended Warranty |
| 71C20Y0 | Lexmark CS/CX730, 735 Yellow Return Programme 5K Toner Cartridge | 2372885 | CX730 2 Year Parts Only Extended Warranty |
| 71C20K0 | Lexmark CS/CX730, 735 Black Return Programme 5K Toner Cartridge | 2372886 | CX730 3 Year Parts Only Extended Warranty |
| 71C2HC0 | Lexmark CS/CX730 Cyan Return Programme 10.5K Toner Cartridge | 2372887 | CX730 4 Year Parts Only Extended Warranty |
| 71C2HM0 | Lexmark CS/CX730 Magenta Return Programme 10.5K Toner Cartridge | 2372888 | CX730 5 Year Parts Only Extended Warranty |
| 71C2HY0 | Lexmark CS/CX730 Yellow Return Programme 10.5K Toner Cartridge | 2372889 | CX730 6 Year Parts Only Extended Warranty |
| 71C2HK0 | Lexmark CS730, 735, CX730 Black Return Programme 22K Toner Cartridge | 2372890 | CX730 1 Year Renewal Parts Only |
| | | 2372891 | CX730 2 Year Renewal Parts Only |
| | | 2372892 | CX730 3 Year Renewal Parts Only |
| | | 2372893 | CX730 4 Year Renewal Parts Only |
| | | 2372914 | CX730 Per Call Preventive Maintenance w/ Kit |
| P/N | Paper Handling | | |
| 40C2100 | CS72x, CX725 550-Sheet Drawer (incl. Tray) | | |
| 47C4590 | Convenience Stapler | | |
| P/N | Furniture | | |
| 40C2300 | CS72x, CX725 Printer Stand (adjustable height) | | |
| P/N | Memory Options | | |
| 27X0400 | 500+ GB Hard Disk | | |
| 57X9528 | Intelligent Storage Drive (ISD) | | |
| P/N | Application Solutions | | |
| 57X0300 | Contact Authentication Device | | |
| 57X0301 | Contactless Authentication Device | | |
| 82S1204 | Bar Code License | | |
| 82S1203 | IPDS License | | |
| 57X0235 | Contactless Front Solutions Module (Primary) | | |
| 57X0225 | Desktop Contactless Reader | | |
| P/N | Connectivity | | |
| 27X6410 | Lexmark MarkNet N8372 802.11 a/b/g/n/ac Wireless Print Server | | |
| 57X7040 | English Keyboard Kit | | |
| 27X0823 | MarkNet N8370 Wireless for CS720, CS725, CX725 | | |
| 37X6350 | Analog Fax Card | | |
| 1021294 | USB Cable (2 meter) | | |
| SPD0002 | Surge protective device | | |
| P/N | Extended Warranties | | |
| 2372859 | CX730 1 Year Onsite Repair NBD Warranty | | |
| 2372860 | CX730 2 Year Onsite Repair NBD Warranty | | |
| 2372861 | CX730 3 Year Onsite Repair NBD Warranty | | |
| 2372862 | CX730 4 Year Onsite Repair NBD Warranty | | |