

Lexmark CX730de

The Lexmark CX730de is designed for performance, security and ease of use for mid-to-large workgroups at speeds of up to 40 pages per minute*.

Part Number

47C9520

Print Technology

Colour Laser

Function

Colour Copying, Colour Printing, Colour Scanning, Colour Network Scanning, Trusted Platform Module (TPM), The Trusted Platform Module (TPM) is not available in some countries.

Workgroup Size

Medium-Large Workgroup

Touch Screen Display

Yes

Display

Lexmark e-Task 17.8 cm (7-inch) colour touch screen

Print Speed (A4, Black)

Do 40 ppm⁶

Print Speed (A4, Colour)

Do 40 ppm⁶

Print Speed (A4, Black) Duplex

Do 30.5 spm⁶

Time to First Page (Black) As fast as

Za samo 6.4 seconds

Time to First Page (Colour) As fast as

Za samo 7.0 seconds

Duplex (2-sided) Printing

Integrated Duplex

Print Resolution, Black

1200 x 1200 dpi, 4800 CQ (2400 x 600 dpi)

Print Resolution, Colour

 $1200 \times 1200 \text{ dpi}, 4800 \text{ CQ } (2400 \times 600 \text{ dpi})$

Copy Speed (A4, Black)

Do 39.5 cpm⁶

Copy Speed (A4, Colour)

Do 39.5 cpm⁶

Time to First Copy (Black) as fast as

Za samo 6.7 seconds

Time to First Copy (Colour) as fast as

Za samo 7.3 seconds

Reduce / Enlarge Range

25 - 400 %

A4/Ltr Simplex Scan Speed (Black)

Do 40 / 42 sides per minute

A4/Ltr Simplex Scan Speed (Colour)

Do 40 / 42 sides per minute

A4/Ltr Duplex Scan Speed (Black)

Do 80 / 84 sides per minute

A4/Ltr Duplex Scan Speed (Colour)

Do 80 / 84 sides per minute

Scan Area, Maximum (mm)

216 x 356 mm

ADF Scan

DADF (single pass Duplex)

Scanner Type

Flatbed scanner with ADF

Scan Technology

Trilinear CIS

Scan Resolution, Enhanced

Up to 600 X 600 dpi

Scan Resolution, Optical

Up to 600 dpi

Scan File Formats (Send as)

JPEG, JPG, PDF, Secure PDF, TIFF, Archival PDF (A-1a, A-1b), Searchable PDF (optional OCR with 1GB RAM and hard disk required), Highly compressed PDF (1GB RAM and hard disk required)

Scan Destinations

e-mail, FTP, USB Flash drive, USB or Network connected computer, Lexmark Document Solutions Suite (LDSS)

Processor Speed

Quad Core 1.2 GHz

Memory, Standard

2048 MB

Memory, Maximum

2048 MB

Hard Disk

Intelligent Storage Drive (optional); Magnetic Hard Disk (optional)

Apple Operating Systems Supported

Support is provided through AirPrint and AirScan only

Citrix MetaFrame

Microsoft Windows Server 2012 R2
Datacenter Edition running Citrix XenApp
7.5, 6, 7, 8, 9, 11, 12, 13, 14, 15, 16, Microsoft
Windows Server 2012 Datacenter Edition
running Citrix XenApp 7.5, 6, 7, 8, 9, 11, 12,
13, 14, 15, 16, Microsoft Windows Server 2012
Foundation running Citrix XenApp 6.0, 6.5,
Microsoft Windows Server 2012 Essentials
running Citrix XenApp 6.0, 6.5, Microsoft
Windows Server 2012 Standard running Citrix
XenApp 6.0, 6.5

Linux Operating Systems Supported

Ubuntu 20.04, Debian 10, SUSE Linux Enterprise Server 12 SP5, OpenSUSE 15.2, Debian 11, Ubuntu 22.04, Fedora 36, Fedora 37, SUSE Linux Enterprise Server 15 SP4, OpenSUSE 15.4, Red Hat Linux 8.7, Red Hat Linux 9.1

Microsoft Windows Operating Systems Supported

Windows 7, Windows 7 x64, Windows 8, Windows 8 x64, Windows Server 2012, Windows Server 2012 R2, Windows RT, Windows 10, Windows Server 2016, Windows Server 2019, Windows Server 2022, Windows 11

Novell Operating Systems Supported

Novell NetWare 6.5 Open Enterprise Server, Novell Open Enterprise Server 2 on SUSE Linux Enterprise Server 10 SP4, Novell Open Enterprise Server 11 on SUSE Linux Enterprise Server 11, Novell Open Enterprise Server 11 (SP3) on SuSE Linux Enterprise Server 12 SP1 (x86 and x64), Novell Open Enterprise Server 15 (SP1) on SuSE Linux Enterprise Server 11 SP4 (x86 and x64)

Included Paper Handling

550-Sheet Input, 100-Sheet Multipurpose Feeder, Integrated Duplex, 300-Sheet Output Bin

Optional Paper Handling

550-Sheet Tray

Paper Input Capacity, Standard

Do 650 pages 75 gsm bond

Paper Input Capacity, Maximum

Do 2850 pages 75 gsm bond

Paper Output Capacity, Standard Do 300 pages 75 gsm bond

Do 300 pages 75 gsill bolk

Paper Output Capacity, Maximum

Do 300 pages 75 gsm bond

Paper Weight Range Supported - Standard Tray (gsm)

60 - 218 gsm

Paper Weight Range Supported -Multipurpose Feeder (gsm)

60 - 218 gsm

Integrated Tray Card Stock Upper limit (grain long)

Index Bristol - 199 gsm (110 lb), Tag - 163 gsm (100 lb), Cover - 176 gsm (65 lb)

Integrated Tray Card Stock Upper limit (grain short)

Index Bristol - 199 gsm (110 lb), Cover - 216 gsm (80 lb), Tag - 203 gsm (125 lb)

ADF

100-Sheet Automatic Document Feeder

ADF Paper Input Capacity

Do 100 pages 75 gsm bond

ADF Paper Output Capacity

Do 100 pages 75 gsm bond

Finishing Option

No

Number of Paper Inputs, Standard

Number of Paper Inputs, Maximum 6

Media Types Supported

Card Stock, Envelopes, Paper Labels, Plain Paper, Vinyl Labels, Banner Paper, Refer to the Paper & Specialty Media Guide

Media Sizes Supported

10 Envelope, 7 3/4 Envelope, 9 Envelope, A4, A5, B5 Envelope, C5 Envelope, DL Envelope, Executive, Folio, JIS-B5, Legal, Letter, Statement, Universal, Oficio, A6

Caster Base

No

Standard Connectivity

One Internal Card Slot, USB 2.0 Specification Hi-Speed Certified (Type B), Gigabit Ethernet (10/100/1000), Front USB 2.0 Specification Hi-Speed Certified port (Type A), Rear Hi-Speed USB port Compatible with USB 2.0 Specification (Type A)

Optional Network Ports

Internal MarkNet N8370 802.11b/g/n/a Wireless. NFC

Direct USB

Yes

Ethernet Network

Voc

Wireless

Wireless Option

Network Protocol Support

TCP/IP IPv4, TCP/IP IPv6, TCP, UDP, IPSEC w/ IPv4, IPSEC w/ IPv6, ICMP, IGMP

Network Printing Methods

LPR/LPD, Direct IP (Port 9100), Enhanced IP (Port 9400), Secure IP (Port 96xx), FTP, ThinPrint .print integration, IPP 1.0, 1.1, 2.0 (Internet Printing Protocol), Microsoft Web Services WSD, Pull Printing

Network Management Protocols¹

HTTP, HTTPs (SSL/TLS), SNMPv1, SNMPv2c, SNMPv3, WINS, IGMP, BOOTP, RARP, APIPA (AutoIP), DHCP, ICMP, DNS, DDNS, mDNS, ARP, NTP, Telnet, Finger,

Network Security

SNMPv3, 802.1x Authentication: MD5, MSCHAPv2, LEAP, PEAP, TLS, TTLS, Certificate Management, SSL Cipher Configuration, TCP/UDP Port Access Control, Security Port Lockdown, IPSEC Support (IPv4/ IPv6)

Printable Area (metric)

4.2 mm of the top, bottom, right and left edges (within)

Printer Languages (Standard)

PCL 6 Emulation, Personal Printer Data Stream (PPDS), PostScript 3 Emulation, Direct Image, PDF 1.7 emulation, PCL 5

Fonts and Symbol Sets

158 scalable PostScript fonts, 39 scalable PPDS fonts, 5 PPDS bitmap fonts, For more information, refer to the Technical Reference., 89 scalable PCL 6 fonts, 2 PCL 6 bitmap fonts

Laser Cartridge Yields (up to)⁵

, 22,000-page Black High Yield Cartridge, 10,500-page Colour (CMY) High Yield Cartridges

Imaging Unit Estimated Yield

Do 150000 pages, based on 5 average letter/A4 size pages per print job and $^{\sim}$ 5% coverage for CS/CX96x, CX83x, CX95x, and MX95x printer series, or based on 3 average letter/A4 size pages per print job and $^{\sim}$ 5% coverage for all other printers 4

Cartridge(s) Shipping with Product

5,000-page (CMYK) Return Programme Toner Cartridges

Replacement Cartridges:

Product functions only with replacement cartridges designed for use in a specific geographical region. See www.lexmark.com/regions for more details.

Packaged Size (mm - H x W x D)

838 x 700 x 735 mm

Packaged Weight, kg

52.5 kg

Size (mm - H x W x D)

621 x 479 x 533 mm

Weight

39 kg

Noise level (Idle mode)

14 dBA

Noise Level (Print), Operating

52 dBA

Duplex Print Noise Level, Operating

53 dBA

Noise Level (Copy), Operating

55 dBA

Noise Level (Scan), Operating

51 dBA

Quiet Mode

47 dBA

ENERGY STAR

Yes

Average Power (Hibernate Mode)

0.1 watts

Average Power (Sleep Mode)

1 watts

Average Power (Ready Mode)

61 watts

Average Power (Printing)

630 watts

Average Power while Printing Duplex

520 watts

Average Power (Copying)

640 watts

Average Power (Scanning)

44.5 watts

ENERGY STAR Typical Electricity

Consumption (TEC)

0.55 kilowatt-hours per week

Product Guarantee1-Year Onsite Service, Next Business Day

Product Certifications

ENERGY STAR, ICES-003 Class A, BSMI Class A, VCCI Class A, FCC Class A, NOM-032, UL, cUL, NOM, US FDA/CDRH, IEC 60825-1, CB Report, ISO-532B, CE (EU) DoC, EFTA (CE), KC logo, CCC, C-tick DoC, EuP, CECP, CEL, EC 1275/2008, ECMA-370, TED, SII, TER, SABS, UL-AR, GS Mark, Green Dot, ISO-9296, COC, EPEAT, China Green Product (CGP), Mopria Certified, Blue Angel / RAL-UZ 219

Maximum Monthly Duty Cycle

Do 120000 pages per month³

Recommended Monthly Page Volume

1500 - 15000 pages²

Specified Operating Environment

Humidity: 8 to 80% Relative Humidity, Temperature: 10 to 32°C (50 to 90°F), Altitude: 0 - 2896 Metres (9,500 Feet)

License/Agreement Terms

Printers are sold subject to certain license/ agreement conditions. See www.lexmark.com/ printerlicense for details.

Country of Origin

China (PRC), Mexico

UNSPSC Code

43212110

based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage.

3"Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs.

⁴Actual Yield may vary based on other factors such as device speed, paper size and feed orientation, toner coverage, tray source, percentage of black-only printing and average print job complexity.

⁵Average continuous black or continuous composite CMY declared cartridge yield up to this number of standard pages in accordance with ISO/IEC 19798.

 $^6\mathrm{Print}$ and copy speeds measured in accordance with ISO/ IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds.

¹This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (http://www.openssl.org/)

²"Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings



P/N	Kertridži sa tonerom	P/N	Produžene garancije
71C0Z10	Lexmark CS/CX730, 735, C/XC4342, C/XC4352 Black 150K Imaging Unit	2372864	CX730 6-Year Onsite Repair NBD Warranty
71C0Z50	Lexmark CS/CX730, 735, C/XC4342, C/XC4352 Colour (CMY) 150K Imaging Unit	2372865	CX730 1-Year Renewal Onsite Repair, Response Time Next Business Day
71C0W00	Lexmark CS/CX730, 735, C/XC4342, C4352 170K Waste Container	2372866	CX730 2-Year Renewal Onsite Repair, Response Time Next
71C0H20	Lexmark CS/CX730 Cyan 10.5K Toner Cartridge	2372867	Business Day CX730 3-Year Renewal Onsite
71C0H30	Lexmark CS/CX730 Magenta 10.5K Toner Cartridge		Repair, Response Time Next Business Day
71C0H40	Lexmark CS/CX730 Yellow 10.5K Toner Cartridge	2372868	CX730 4-Year Renewal Onsite Repair, Response Time Next
71C0H10	Lexmark CS730, 735, CX730 Black 22K Toner Cartridge	2372869	Business Day CX730 1-Year Post Warranty Onsite
71C80C0	Lexmark CS/CX730, 735 Cyan Return Programme 5K Toner Cartridge	1 2372884	Repair Next Business Day CX730 1-Year Parts Only Extended
71C80M0	Lexmark CS/CX730, 735 Magenta Return Programme 5K Toner Cartridge	2372885	Warranty CX730 2-Year Parts Only Extended Warranty
71C80Y0	Lexmark CS/CX730, 735 Yellow Return Programme 5K Toner	2372886	CX730 3-Year Parts Only Extended Warranty
71C80K0	Cartridge Lexmark CS/CX730, 735 Black Return Programme 5K Toner	2372887 2372888	CX730 4-Year Parts Only Extended Warranty CX730 5-Year Parts Only Extended
71C8HC0	Cartridge Lexmark CS/CX730 Cyan Return	2372889	Warranty CX730 6-Year Parts Only Extended
71C8HM0	Programme 10.5K Toner Cartridge Lexmark CS/CX730 Magenta Return		Warranty CX730 1-Year Renewal Parts Only
71C8HY0	Programme 10.5K Toner Cartridge Lexmark CS/CX730 Yellow Return	2372891 2372892	CX730 2-Year Renewal Parts Only CX730 3-Year Renewal Parts Only
71C8HK0	Programme 10.5K Toner Cartridge Lexmark CS730, 735, CX730 Black	2372893	CX730 4-Year Renewal Parts Only
	Return Programme 22K Toner Cartridge		
P/N	Manipulisanje papirom	=	
40C2100 47C4590	550-Sheet Tray Convenience Stapler		
P/N	Nameštaj	_	
40C2300	Adjustable Stand		
P/N	Opcije memorije	_	
27X0400	500+ GB Hard Disk		
57X9528 57X0070	Intelligent Storage Drive (ISD) Removable Hard Disk Enclosure Kit		
P/N	Rešenja za aplikacije	_	
57X0300	Contact Authentication Device		
57X0301	Contactless Authentication Device		
82S1204 82S1203	Bar Code License IPDS License		
57X0235	Contactless Front Solutions Module		
57X0225	(Primary Choice) Desktop Contactless Reader		
P/N	Povezivanje		
27X6410	Lexmark MarkNet N8372 802.11 a/b/g/n/ac Wireless Print Server	_	
57X7040 27X0823	English Keyboard Kit MarkNet N8370 Wireless for CS720,		
37X6350 1021294	CS725, CX725 Analog Fax Card USB (2 Meter) Cable		
P/N 2372859	Produžene garancije CX730 1-Year Onsite Repair NBD	_	
2372860	Warranty CX730 2-Year Onsite Repair NBD Warranty		
2372861	Warranty CX730 3-Year Onsite Repair NBD Warranty		
2372862	CX730 4-Year Onsite Repair NBD Warranty		
2372863	CX730 5-Year Onsite Repair NBD Warranty		